



TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies



PRODUCT DESCRIPTION

[Home](#) / [Trade Professionals](#) / Tulle



TULLE

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Taupe

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream , Taupe
Material	3D Wall , Fabric
Finish	Matte
Price	\$

Tulle quantity

Add to cart

SKU: tulle

Categories: [Ceramic Tile](#), [Trade Professionals](#)

TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

RELATED PRODUCTS



SILK

\$0.00



STEAMSHIP

\$0.00



CREFOR

\$0.00