

VAIL AVAILABLE SIZES

SizesTypeStyleFinishThicknessSqft/CartonPieces/BoxRecommended Grout Joint8x40PorcelainNon-RectifiedMatte3/8"15.077VAIL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1





PRODUCT DESCRIPTION

Home / Porcelain & Ceramic Tile / Vail



VAIL

\$0.00

- <u>Description</u><u>Additional information</u>

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Oak Walnut

RECOMMENDED INSTALLATIONS

Wall Floor Exterior

SHARE THIS STYLE



GENERATE PDF

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Color	<u>Beige & Cream, Brown</u>
Finish	<u>Matte</u>
Material	Wood
Price	<u>\$</u>
Vail quantity	

1

Add to cart

SKU: vail

Categories: Porcelain & Ceramic Tile, Trade Professionals

VAIL AVAILABLE SIZES

SizesTypeStyleFinish Thickness Sqft/Carton Pieces/BoxRecommended Grout Joint8x40Porcelain Non-Rectified Matte3/8"15.077

VAIL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1

RELATED PRODUCTS



STONETREND

\$0.00



CREFOR

\$0.00



SARK STEEL

\$0.00