VAIL AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte	3/8"	15.07	7	

VAIL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1

PRODUCT DESCRIPTION

VAIL

$0.00

- Description
- Additional information

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Oak
Walnut

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



GENERATE PDF

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Color	Beige & Cream, Brown
Finish	Matte
Material	Wood
Price	$

Vail quantity
1

Add to cart

SKU: vail

Categories: Porcelain & Ceramic Tile, Trade Professionals

VAIL AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte	3/8"	15.07	7	

VAIL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant

Physical Properties	Standard	Results
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1

RELATED PRODUCTS

- ### BERSE

  $0.00

- ### CEMENTI

  $0.00

- ### MANDALAY

  $0.00