



SARKOTILE

VAIL AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Cartron	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte	3/8"	15.07	7	

VAIL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1



PRODUCT DESCRIPTION

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Oak

Walnut

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall

Floor

Exterior

SHARE THIS STYLE

[GENERATE PDF](#)