



## VALDI AVAILABLE SIZES

| Sizes | Type      | Style                       | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|-----------------------------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Non-Rectified               | Matte  | 3/8"      | 14.25       | 7          | Min. 1/8"               |
| 12x12 | Porcelain | Mosaic 2"x4"<br>Herringbone | Matte  | 3/8"      | 8.47        | 7          |                         |

## VALDI TILE PERFORMANCE DATA

| Physical Properties  | Standard          | Results        |
|--|-------------------|----------------|
| Water Absorption   | ISO 10545-3       | $E \leq 0.5\%$ |
| Breaking Strength  | ISO 10545-4       | $> 250$        |
| MOH's Hardness   | EN 0              | 5              |
| Chemical Resistance<br>(Acid & Bases)<br>(Household Chemicals) | ISO 10545-13      | Unaffected     |
| Frost Resistance   | ISO 10545-12      | Resistant      |
| PEI-Glazed Tiles   | ISO 10545-7       | 5              |
| Minimum Bond Strength (PSI)                                    | C482              | $\geq 50$ psi  |
| Dynamic Coefficient of Friction                                | D.C.O.F. $> 0.42$ | $\geq 0.42$    |
| Shade and Texture Rating                                       | CTDA "V"          | V3             |
| Facial Dimensions  | ISO 10545-2       | Pass           |
| Range of Thickness   | ISO 10545-2       | Pass           |
| Warping  | ISO 10545-2       | Pass           |
| Wedging  | ISO 10545-2       | Pass           |



# PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / Valdi





## VALDI

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---

### SHARE THIS STYLE



## ADDITIONAL INFORMATION

|                 |                       |
|-----------------|-----------------------|
| <b>Color</b>    | Gray, White           |
| <b>Material</b> | Stone                 |
| <b>Material</b> | <a href="#">Stone</a> |
| <b>Finish</b>   | <a href="#">Matte</a> |
| <b>Price</b>    | <a href="#">\$</a>    |

Valdi quantity

Add to cart

SKU: valdi

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## VALDI AVAILABLE SIZES

| Sizes | Type      | Style                    | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|--------------------------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Non-Rectified            | Matte  | 3/8"      | 14.25       | 7          | Min. 1/8"               |
| 12x12 | Porcelain | Mosaic 2"x4" Herringbone | Matte  | 3/8"      | 8.47        | 7          |                         |

## VALDI TILE PERFORMANCE DATA

| Physical Properties  | Standard        | Results        |
|--|-----------------|----------------|
| Water Absorption   | ISO 10545-3     | $E \leq 0.5\%$ |
| Breaking Strength  | ISO 10545-4     | > 250          |
| MOH's Hardness   | EN  0           | 5              |
| Chemical Resistance<br>(Acid & Bases)<br>(Household Chemicals) | ISO 10545-13    | Unaffected     |
| Frost Resistance   | ISO 10545-12    | Resistant      |
| PEI-Glazed Tiles   | ISO 10545-7     | 5              |
| Minimum Bond Strength (PSI)                                    | C482            | $\geq 50$ psi  |
| Dynamic Coefficient of Friction                                | D.C.O.F. > 0.42 | $\geq 0.42$    |
| Shade and Texture Rating                                       | CTDA "V"        | V3             |
| Facial Dimensions  | ISO 10545-2     | Pass           |
| Range of Thickness   | ISO 10545-2     | Pass           |
| Warping  | ISO 10545-2     | Pass           |
| Wedging  | ISO 10545-2     | Pass           |

## RELATED PRODUCTS



## MONACO

\$0.00



## PULPIS

\$0.00



**ACID**

\$0.00