



## VALDI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	14.25	7	Min. 1/8"
12x12	Porcelain	Mosaic 2"x4" Herringbone	Matte	3/8"	8.47	7	

## VALDI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	> 250
MOH's Hardness	EN 0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	5
Minimum Bond Strength (PSI)	C482	$\geq 50$ psi
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	$\geq 0.42$
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Valdi



### VALDI

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

#### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

#### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	Gray, White
<b>Material</b>	Stone
<b>Material</b>	<a href="#">Stone</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	<a href="#">\$</a>

Valdi quantity

Add to cart

SKU: valdi

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## VALDI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	14.25	7	Min. 1/8"
12x12	Porcelain	Mosaic 2"x4" Herringbone	Matte	3/8"	8.47	7	

## VALDI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	> 250
MOH's Hardness	EN   0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	5

## Physical Properties

	Standard	Results
Minimum Bond Strength (PSI)	C482	≥50 psi
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass

## RELATED PRODUCTS

- 

### SARK STEEL

\$0.00

- 

### METRO

\$0.00

- 

### CEMENTONIA

\$0.00