VULSINI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	14	7	Min. 1/16"

VULSINI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E<0.5%
Breaking Strength	ISO 10545-4	> 1600 N
MOH's Hardness	EN|0|	8
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 15045-14	3

PRODUCT DESCRIPTION

VULSINI

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Bianco
Grigio
Nero

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



GENERATE PDF

ADDITIONAL INFORMATION

Color	Gray, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Material	Stone
Finish	Matte
Price	$

Vulsini quantity
1

Add to cart

SKU: vulsini

Categories: Porcelain & Ceramic Tile, Trade Professionals

VULSINI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	14	7	Min. 1/16"

VULSINI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	E<0.5%
Breaking Strength	ISO 10545-4	> 1600 N
MOH's Hardness	EN|0|	8
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 15045-14	3

RELATED PRODUCTS

- ### TIMBER

  $0.00

- ### STEAMSHIP

  $0.00

- ### SILK

  $0.00