WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA
Stain Resistance	ISO 10545-14	Class 5

PRODUCT DESCRIPTION

WEATHERED WOOD

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Agent
Magma

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown
Material	Wood
Finish	Matte
Price	$

Weathered Wood quantity
1

Add to cart

SKU: weathered-wood

Categories: Porcelain & Ceramic Tile, Trade Professionals

WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA

	Standard	Results
Stain Resistance	ISO 10545-14	Class 5

RELATED PRODUCTS

-

BI’MAN

$0.00

-

MANDALAY

$0.00

-

CEMENTI

$0.00