



WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA
Stain Resistance	ISO 10545-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Weathered Wood



WEATHERED WOOD

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Agent
Magma

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown
Material	Wood
Finish	Matte
Price	\$

Weathered Wood quantity

Add to cart

SKU: weathered-wood

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA

RELATED PRODUCTS



TIMBER

\$0.00



CORCHO

\$0.00



TIVOLI

\$0.00