



## WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

## WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA
Stain Resistance	ISO 10545-14	Class 5



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Weathered Wood



## WEATHERED WOOD

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

#### AVAILABLE COLORS

Agent  
Magma

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

#### RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

#### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	<a href="#">Beige &amp; Cream, Brown</a>
<b>Material</b>	<a href="#">Wood</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	<a href="#">\$</a>

Weathered Wood quantity

Add to cart

SKU: weathered-wood

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## WEATHERED WOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	19.12	9	Min. 1/8"

## WEATHERED TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	.1%
Breaking Strength	ISO 10545-4	1800-2400 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Conforms to standard UA

## RELATED PRODUCTS

- 

### **COLORADO**

\$0.00

- 

### **CEMENTONIA**

\$0.00

- 

### **PULPIS**

\$0.00