WOODLOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	17	8	Min. 1/8"

WOODLOT TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E ≤ 0.1%
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN|0|	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

PRODUCT DESCRIPTION

WOODLOT

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Argent
Cenere
Moka
Plomo
Taupe

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown, Taupe, White
Material	Wood
Finish	Matte
Price	$

Woodlot quantity
1

Add to cart

SKU: woodlot

Categories: Porcelain & Ceramic Tile, Trade Professionals

WOODLOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	17	8	Min. 1/8"

WOODLOT TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E ≤ 0.1%
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN|0|	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

RELATED PRODUCTS

- ## CREFOR

  $0.00

- ## BEACHWOOD

  $0.00

- ## CORK

  $0.00