



## WOODLOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	17	8	Min. 1/8"

## WOODLOT TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.1\%$
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN   0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Woodlot



# WOODLOT

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

## AVAILABLE COLORS

Argent  
Cenere  
Moka  
Plomo  
Taupe

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

## RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

---

## SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

Color	<a href="#">Beige &amp; Cream</a> , <a href="#">Brown</a> , <a href="#">Taupe</a> , <a href="#">White</a>
Material	<a href="#">Wood</a>
Finish	<a href="#">Matte</a>
Price	\$

Woodlot quantity

Add to cart

SKU: woodlot

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## WOODLOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
9x34	Porcelain	Non-Rectified	Matte	5/16"	17	8	Min. 1/8"

# WOODLOT TILE PERFORMANCE DATA

	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.1\%$
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

## RELATED PRODUCTS



### METRO

\$0.00



### ACID

\$0.00



### CORK

\$0.00